The New and Improved **FISCHER Panda AC 5000** MARINE GENERATOR

The New Fischer Panda AC 5000 now features a twin-cylinder Kubota Diesel engine for longevity and reliability.

Fischer Panda Generators are the ideal choice for the professional sailor or power boater. When space is tight, weight is critical or noise is an issue, many boaters choose Fischer Panda. The new Fischer Panda AC 5000 marine generator is powered by the reliable freshwater-cooled Kubota twin-cylinder diesel engine and our superior asynchronous water-cooled alternator.

All Fischer Panda generators come standard with 100% freshwater cooling, superior sound enclosure, bulkhead external connections, remote fuel lift pump and remote control panel.

Depending upon the kilowatt size Fischer Panda Generators can weigh up to 50% less than a conventional generator and are up to 30% smaller in size.









351 S. Andrews Ave., Pompano Beach, FL 33069

Call (800) 508-6494

Visit us at www.fischerpanda.com or e-mail us at sales@fischerpanda.com




FEATURES INCLUDE:

- Less weight, size and noise
- Extremely quiet (54dba@7meter)
- Direct driven fresh water-cooled Asynchronous Alternator
- Robust twin-cylinder Kubota diesel engine
- VCS electronic govenor provides excellent voltage stability
- Integrated internal booster enabling high inductive load starting
- Gear driven raw water pump
- Safety shutdowns for all critical functions
- Self protected against overload
- Ignition Protection for gas powered boats
- Comes complete with harnesses, remote control panel, sound enclosure and remote fuel lift pump
- 5 Year limited warranty

FISCHER PANDA AC 5000 SPECIFICATIONS	
Frequency	50 Hz
Voltage	230V
Current Max.	21A
Peak Output	4.8 kW
Continuous Output	4.2 kW
Engine Type	Kubota / Z•482
Cylinders	2 cyl / 8.8 hp
Displacement	479 ccm / 21.23 cu. in.
Cooling	H / E
Dimensions (LWH)	21.25 x 17.5 x 21.9 inches
Weight (Wet)	268 lbs
Noise Level	54 dBa @ 7 Meters

^{*}Generator set standard at 80% output for continuous use, for peak output contact Fischer Panda.

Remote Panel



OPTIONAL ACCESSORIES

External Soft Motor Mounts

External Soft Motor Mounts for extra smooth operation.



Vented Loop

(anti-syphon valve)
Recommended for all
installations. Prevents water
from siphoning back to the
engine and minimizes potential
electrolysis. Made with a
stainless steel tube and nylon
valve for long life and easy
service.



Gas Separator


Exhaust water separator provides very low back pressure and extra quiet exhaust noise.




Low Profile Muffler

Low inlet muffler for installations where the muffler cannot be installed lower than the genset.









351 S. Andrews Ave., Pompano Beach, FL 33069

Call (800) 508-6494

Visit us at www.fischerpanda.com or e-mail us at sales@fischerpanda.com

