



AGT 10000



FischerPanda®

SPECIFICATIONS	
Generator	Panda 10000 PSC Liquid-cooled AC Generator
Constant Output	7.5 kW at 3000m / +50°C
Output Voltage	230V / 400V 3- phase 50 Hz
Output Current	3 x 11 A
Start System	24V Electrical
Engine Manufacturer	Kubota
Engine Type	D902
Engine Cylinders	3
Engine Operating Temp. Range	-32°C up to +55°C (other temperature ranges on request)
Fuel Types	F 34, F 54 ,Standard automotive diesel fuel, kerosene, JP 8, JP 5, JET A
Approx. Fuel Consumption ¹⁾	1.5 - 5.0 l/h
Fuel Supply	Integrated Fuel Tank (60 litre capacity)
Frame / Mounting	Self contained unit mounted on frame with forklift pockets
Cooling System	Integrated radiator and fans mounted vertically for cooling
Instrumentation & Electrical	Integrated electrical cabinet with instruments and connections
Approx APU weight*	600 kg (dry)

Due to our policy of continual product development, we reserve the right to alter these specifications without notice.



FischerPanda®



SMALL



LIGHT



QUIET

351 S. Andrews Avenue
Pompano Beach, FL 33069
U.S.A.

www.FischerPanda.com/Military

Phone: 954-462-2800
Fax: 954-462-2801
Toll-free: 800-508-6494

MilSupport@FischerPanda.com

